

TYRES

Product group	Tyres
Item number	12426282
Valid tyre size	360 / 70 R 28
LI / SI / PR	125 A8 / 125 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker





Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.



Technical Informations

Item number	12426282
EAN	3528707610386
Valid tyre size	360 / 70 R 28
LI / SI / PR	125 A8 / 125 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	59,00
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	1,60
Section width (mm)	368
Outer diameter of tyre [mm].	1263
Stat. radius (SLR) [mm]	565
Rolling circumference [mm].	3747
Tread depth (mm)	40,0
Number of lugs	20x2
Lug width (mm)	37
Tyre capacity 75% [ltr.]	153
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A8	1650	40		1,60	
125 B	1650	50		1,60	