

TYRES

Product group	Tyres
Item number	12426355
Valid tyre size	480 / 70 R 30
LI / SI / PR	141 A8 / 141 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker



Bohnenkamp
■ ■ ● Moving Professionals

Kleber

Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.

Technical Informations

Item number	12426355
EAN	3528703477358
Valid tyre size	480 / 70 R 30
LI / SI / PR	141 A8 / 141 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	110,00
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	495
Outer diameter of tyre [mm].	1483
Stat. radius (SLR) [mm]	662
Rolling circumference [mm].	4400
Tread depth (mm)	48,0
Number of lugs	20x2
Lug width (mm)	44
Tyre capacity 75% [ltr.]	316
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A8	2575	40		1,60	
141 B	2575	50		1,60	