# Bohnenkamp Moving Professionals

## **TYRES**

| Product group   | Tyres          |  |
|-----------------|----------------|--|
| Item number     | 12426356       |  |
| Valid tyre size | 420 / 70 R 30  |  |
| LI / SI / PR    | 134 A8 / 131 B |  |
| TL/TT           | TL             |  |
| Brand           | Kleber         |  |
| Tread pattern   | Fitker         |  |



## Notes and features

- Maximum traction due to optimised lug shape. .
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone. •
- Long service life. •

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

# **Technical Informations**

| Item number                  | 12426356        |
|------------------------------|-----------------|
| EAN                          | 3528706618291   |
| Valid tyre size              | 420 / 70 R 30   |
| LI / SI / PR                 | 134 A8 / 131 B  |
| TL/TT                        | TL              |
| Brand                        | Kleber          |
| Tread pattern                | Fitker          |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | not necessary   |
| Nettogewicht [kg] (gültig)   | 88,00           |
| Recommended rim size         | W13             |
| Permitted rim size           | W12, DW14L, W14 |
| Maximum air pressure [bar].  | 1,60            |
| Section width (mm)           | 410             |
| Outer diameter of tyre [mm]. | 1399            |
| Stat. radius (SLR) [mm]      | 628             |
| Rolling circumference [mm].  | 4217            |
| Tread depth (mm)             | 41,0            |
| Number of lugs               | 19x2            |
| Tyre capacity 75% [ltr.]     | 205             |
| E-Ready                      | No              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 134 A8 | 2120               | 40           |               | 1,60                        |              |
| 131 B  | 1950               | 50           |               | 1,60                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.