

TYRES

Product group	Tyres
Item number	12426425
Valid tyre size	420 / 85 R 34
LI / SI / PR	142 A8 / 139 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker





Notes and features

- Very good traction through high tread lugs.
- Good self-cleaning.

• Even pressure distribution due to flat tread pattern.



Technical Informations

Item number	12426425
EAN	3528701617770
Valid tyre size	420 / 85 R 34
Alternative size 1	16.9R34
LI / SI / PR	142 A8 / 139 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	105,00
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	442
Outer diameter of tyre [mm].	1581
Stat. radius (SLR) [mm]	708
Rolling circumference [mm].	4693
Tread depth (mm)	46,0
Number of lugs	21x2
Lug width (mm)	41
Tyre capacity 75% [ltr.]	293
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		1,60	
139 B	2430	50		1,60	