Bohnenkamp Moving Professionals

14.03.2025

TYRES

Product group	Tyres
Item number	12426603
Valid tyre size	480 / 70 R 38
LI / SI / PR	145 A8 / 145 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker



Notes and features

- Maximum traction due to optimised lug shape. .
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone. •
- Long service life. •

Bohnenkamp Moving Professionals

Technical Informations

Item number	12426603
EAN	3528701907451
Valid tyre size	480 / 70 R 38
LI / SI / PR	145 A8 / 145 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	129,00
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	492
Outer diameter of tyre [mm].	1697
Stat. radius (SLR) [mm]	765
Rolling circumference [mm].	5045
Tread depth (mm)	48,0
Number of lugs	22x2
Lug width (mm)	48
Tyre capacity 75% [ltr.]	377
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		1,60	
145 B	2900	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.