Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	12426648
Valid tyre size	520 / 85 R 42
LI / SI / PR	157 A8 / 157 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker



Notes and features

- Very good traction through high tread lugs.
- Good self-cleaning.

• Even pressure distribution due to flat tread pattern.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12426648
EAN	3528706560002
Valid tyre size	520 / 85 R 42
Alternative size 1	20.8R42
LI / SI / PR	157 A8 / 157 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	198,00
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	557
Outer diameter of tyre [mm].	1948
Stat. radius (SLR) [mm]	867
Rolling circumference [mm].	5776
Tread depth (mm)	52,0
Number of lugs	21x2
Lug width (mm)	54
Tyre capacity 75% [ltr.]	545
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		1,60	
157 B	4125	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.