

TYRES

Product group	Tyres
Item number	12426650
Valid tyre size	580 / 70 R 38
LI / SI / PR	155 A8 / 155 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker



Bohnenkamp
■ ■ ● Moving Professionals

Kleber

Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.

Technical Informations

Item number	12426650
EAN	3528708575042
Valid tyre size	580 / 70 R 38
LI / SI / PR	155 A8 / 155 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	205,00
Recommended rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	606
Outer diameter of tyre [mm].	1849
Stat. radius (SLR) [mm]	821
Rolling circumference [mm].	5478
Tread depth (mm)	56,0
Number of lugs	20x2
Lug width (mm)	53
Tyre capacity 75% [ltr.]	590
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		1,60	
155 B	3875	50		1,60	