

## TYRES

Product group	Tyres
Item number	12426804
Valid tyre size	270 / 95 R 44
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	Kleber
Tread pattern	Cropker



**Kleber**

## Notes and features

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range.
- Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8.
- It can be used as a FRT (Free Rolling Tyre) on towed vehicles with with a load surcharge of up to 20% at 40 km/h.
- Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected.
- Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage.
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties.

## Technical Informations

Item number	12426804
EAN	3528706995323
Valid tyre size	270 / 95 R 44
Alternative size 1	11.2R44
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	Kleber
Tread pattern	Cropker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	66,00
Recommended rim size	9
Permitted rim size	8, 10
Maximum air pressure [bar].	4,00
Section width (mm)	275
Outer diameter of tyre [mm].	1632
Stat. radius (SLR) [mm]	768
Rolling circumference [mm].	4884
Tread depth (mm)	34,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	144
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		4,00	
142 D	2650	65		4,00	