Bohnenkamp Moving Professionals

14.03.2025

TYRES

Product group	Tyres
Item number	12427050
Valid tyre size	480 / 65 R 28
LI / SI / PR	136 D
TL/TT	TL
Brand	Kleber
Tread pattern	Gripker



Notes and features

- Excellent traction due to innovative lug shape.
- Even weight distribution due to large contact area.
- Good self-cleaning.
- Modern design.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12427050
	12427050
EAN	3528708107885
Valid tyre size	480 / 65 R 28
LI / SI / PR	136 D
TL/TT	TL
Brand	Kleber
Tread pattern	Gripker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	86,00
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	480
Outer diameter of tyre [mm].	1339
Stat. radius (SLR) [mm]	588
Rolling circumference [mm].	3958
Tread depth (mm)	44,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	242
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 D	2240	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.