

TYRES

| Product group | Tyres | |
|-----------------|---------------|--|
| Item number | 12500595 | |
| Valid tyre size | 330 / 40 B 12 | |
| LI / SI / PR | 100 A4, 4 PR | |
| TL/TT | TL | |
| Brand | Carlisle | |
| Tread pattern | Ultra Trac | |





Notes and features

- Special tyre for professional lawn and landscape maintenance.
- Offers very good flotation properties due to a flat contact area and reduced tread gaps.
- Low soil pressure and good traction at the same time.



Technical Informations

| Item number | 12500595 |
|------------------------------|---------------|
| EAN | 5999110828053 |
| Valid tyre size | 330 / 40 B 12 |
| Alternative size 1 | 24x13.00-12 |
| LI / SI / PR | 100 A4, 4 PR |
| TL/TT | TL |
| Brand | Carlisle |
| Tread pattern | Ultra Trac |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 12,10 |
| Recommended rim size | 10.50 |
| Maximum air pressure [bar]. | 1,24 |
| Section width (mm) | 328 |
| Outer diameter of tyre [mm]. | 579 |
| Stat. radius (SLR) [mm] | 259 |
| Rolling circumference [mm]. | 1725 |
| Tread depth (mm) | 7,1 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 100 A4 | 800 | 20 | | 1,20 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.