

TYRES

| Product group | Tyres | |
|-----------------|------------------|--|
| Item number | 13327800 | |
| Valid tyre size | VF 480 / 60 R 28 | |
| LI / SI / PR | 134 D | |
| TL/TT | TL | |
| Brand | Michelin | |
| Tread pattern | XeoBib | |





Notes and features

- Below 1 bar consistent low inflation pressure up to 65 km/h!
- Low soil compaction as a result.

- Saving fuel and time.
- High braking safety and steering precision.



Technical Informations

| Item number | 13327800 |
|------------------------------|------------------|
| EAN | 3528703128755 |
| Valid tyre size | VF 480 / 60 R 28 |
| LI / SI / PR | 134 D |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | XeoBib |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 93,00 |
| Recommended rim size | 16 |
| Maximum air pressure [bar]. | 1,00 |
| Section width (mm) | 488 |
| Outer diameter of tyre [mm]. | 1298 |
| Stat. radius (SLR) [mm] | 567 |
| Rolling circumference [mm]. | 3831 |
| Tread depth (mm) | 45,0 |
| Number of lugs | 19x2 |
| Lug width (mm) | 42 |
| Tyre capacity 75% [ltr.] | 218 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 134 D | 2120 | 65 | | 1,00 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.