

TYRES

Product group	Tyres	
Item number	13327945	
Valid tyre size	480 / 70 R 30	
LI / SI / PR	141 D	
TL/TT	TL	
Brand	Michelin	
Tread pattern	OmniBib	





Notes and features

- Wide-base tyre of the 70 series for medium-performance tractors.
- Outstanding traction and very good self-cleaning.
- Long service life due to high lugs.
- Excellent ride comfort due to flexible casing.



Technical Informations

Item number	13327945
EAN	3528705993511
Valid tyre size	480 / 70 R 30
LI / SI / PR	141 D
TL/TT	TL
Brand	Michelin
Tread pattern	OmniBib
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	109,00
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	498
Outer diameter of tyre [mm].	1482
Stat. radius (SLR) [mm]	656
Rolling circumference [mm].	4388
Tread depth (mm)	48,0
Number of lugs	20x2
Lug width (mm)	41-48
Tyre capacity 75% [ltr.]	316
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 D	2575	65		1,60	