

TYRES

Product group	Tyres
Item number	13328070
Valid tyre size	VF 600 / 60 R 30
LI / SI / PR	162 D / 159 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Michelin AxioBib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

Technical Informations

Item number	13328070
EAN	3528703719687
Valid tyre size	VF 600 / 60 R 30
LI / SI / PR	162 D / 159 E
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	168,00
Recommended rim size	DW20B
Permitted rim size	DW18L
Maximum air pressure [bar].	2,00
Section width (mm)	597
Outer diameter of tyre [mm].	1468
Stat. radius (SLR) [mm]	643
Rolling circumference [mm].	4336
Tread depth (mm)	49,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	381
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 D	4750	65		2,00	
159 E	4375	70		2,00	