

TYRES

Product group	Tyres
Item number	13328223
Valid tyre size	480 / 80 R 46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Michelin Axiobib 2 is designed for tractors within a performance range of 60 to 170 hp.
- The new optimised tread with a lug angle of 45° offers very good traction transmission to the ground.
- Its particularly high tread depth ensures a long service life for the tyre.
- Thanks to the additional rubber lip along the tread centre, the tyre offers very good self-cleaning properties.
- The angle of the lugs and a rubber reinforcement on the tyre shoulder deflect stubble and protect the tyre from damage.

Technical Informations

Item number	13328223
EAN	3528706227097
Valid tyre size	480 / 80 R 46
Alternative size 1	18.4R46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	160,00
Recommended rim size	DW16A
Permitted rim size	DW16L, W16A
Maximum air pressure [bar].	2,40
Section width (mm)	486
Outer diameter of tyre [mm].	1945
Stat. radius (SLR) [mm]	891
Rolling circumference [mm].	5804
Tread depth (mm)	52,0
Number of lugs	25x2
Tyre capacity 75% [ltr.]	449
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		2,40	
158 B	4250	50		2,40	