

## TYRES

Product group	Tyres
Item number	13626091
Valid tyre size	280 / 85 R 24
LI / SI / PR	115 A8 / 112 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp  
Moving Professionals



TRELLEBORG

## Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

**Technical Informations**

<b>Item number</b>	13626091
<b>EAN</b>	8059971013177
<b>Valid tyre size</b>	280 / 85 R 24
<b>Alternative size 1</b>	11.2R24
<b>LI / SI / PR</b>	115 A8 / 112 B
<b>TL/TT</b>	TL
<b>Brand</b>	Trelleborg
<b>Tread pattern</b>	TM600
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	not necessary
<b>Nettogewicht [kg] (gültig)</b>	43,50
<b>Recommended rim size</b>	10
<b>Permitted rim size</b>	8, 9
<b>Maximum air pressure [bar].</b>	1,60
<b>Section width (mm)</b>	292
<b>Outer diameter of tyre [mm].</b>	1086
<b>Stat. radius (SLR) [mm]</b>	494
<b>Rolling circumference [mm].</b>	3276
<b>Tread depth (mm)</b>	39,0
<b>Number of lugs</b>	21x2
<b>Lug width (mm)</b>	27
<b>Tyre capacity 75% [ltr.]</b>	98
<b>E-Ready</b>	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
115 A8	1215	40		1,60	
112 B	1120	50		1,60	