

TYRES

Product group	Tyres
Item number	13626110
Valid tyre size	320 / 85 R 24
LI / SI / PR	122 A8 / 119 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	13626110
EAN	8059971008272
Valid tyre size	320 / 85 R 24
Alternative size 1	12.4R24
LI / SI / PR	122 A8 / 119 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	49,50
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	1,60
Section width (mm)	329
Outer diameter of tyre [mm].	1154
Stat. radius (SLR) [mm]	515
Rolling circumference [mm].	3465
Tread depth (mm)	41,0
Number of lugs	20x2
Lug width (mm)	34
Tyre capacity 75% [ltr.]	140
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40		1,60	
119 B	1360	50		1,60	