

## **TYRES**

Product group	Tyres
Item number	13626162
Valid tyre size	420 / 70 R 24
LI / SI / PR	130 A8 / 130 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700





## Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.



## **Technical Informations**

Item number	13626162
EAN	8059971002584
Valid tyre size	420 / 70 R 24
LI / SI / PR	130 A8 / 130 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	73,50
Recommended rim size	13
Permitted rim size	12, 14
Maximum air pressure [bar].	1,60
Section width (mm)	415
Outer diameter of tyre [mm].	1253
Stat. radius (SLR) [mm]	562
Rolling circumference [mm].	3705
Tread depth (mm)	45,0
Number of lugs	17x2
Lug width (mm)	46
Tyre capacity 75% [ltr.]	229
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 A8	1900	40		1,60	
130 B	1900	50		1,60	