Bohnenkamp Moving Professionals

14.03.2025

TYRES

Product group	Tyres
Item number	13626166
Valid tyre size	480 / 70 R 24
LI / SI / PR	138 A8 / 138 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	ТМ700
Sonderpostenkategorie	DA





Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13626166
Valid tyre size	480 / 70 R 24
LI / SI / PR	138 A8 / 138 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	ТМ700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	87,50
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	468
Outer diameter of tyre [mm].	1300
Stat. radius (SLR) [mm]	580
Rolling circumference [mm].	3875
Tread depth (mm)	47,0
Lug width (mm)	46
Tyre capacity 75% [ltr.]	293
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40		1,60	
138 B	2360	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.