

TYRES

Product group	Tyres	
Item number	13626194	
Valid tyre size	480 / 70 R 26	
LI / SI / PR	139 A8 / 139 B	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM700	
Sonderpostenkategorie	DA	





Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.



Technical Informations

	40000404
Item number	13626194
EAN	4040658063497
Valid tyre size	480 / 70 R 26
LI / SI / PR	139 A8 / 139 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	94,50
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	468
Outer diameter of tyre [mm].	1358
Stat. radius (SLR) [mm]	608
Rolling circumference [mm].	4060
Tread depth (mm)	47,0
Number of lugs	17x2
Lug width (mm)	44
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40		1,60	
139 B	2430	50		1,60	