Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	13626211	
Valid tyre size	540 / 65 R 26	
LI / SI / PR	141 D	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM800	



Notes and features

- Modern agricultural tyre, approved up to 65 km/h.
- Maximum performance in the field due to extra-large contact area.
- High level of comfort. .
- Long service life. •

14.03.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13626211
EAN	8059971003727
	80393/1003/2/
Valid tyre size	540 / 65 R 26
LI / SI / PR	141 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	116,12
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	1,60
Section width (mm)	540
Outer diameter of tyre [mm].	1365
Stat. radius (SLR) [mm]	615
Rolling circumference [mm].	4060
Tread depth (mm)	50,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 D	2575	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.