

TYRES

Product group	Tyres
Item number	13626214
Valid tyre size	620 / 75 R 26
LI / SI / PR	166 A8
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM2000



Notes and features

- Radial tyre for the heaviest harvesters.
- High air volume and large contact area ensure high loading capacities, even at low inflation pressure.
- Large, solid lugs enable optimum slope / lateral stability.
- Special rubber compound minimises tread pattern damage (e.g. by corn stubble).

Technical Informations

Item number	13626214
EAN	8059971014655
Valid tyre size	620 / 75 R 26
Alternative size 1	23.1R26
LI / SI / PR	166 A8
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM2000
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	224,33
Recommended rim size	20
Maximum air pressure [bar].	3,20
Section width (mm)	633
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	716
Rolling circumference [mm].	4850
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A8	5300	40		3,20	