

TYRES

Product group	Tyres
Item number	13626238
Valid tyre size	280 / 85 R 28
LI / SI / PR	118 A8 / 115 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Sonderpostenkategorie	DA



Bohnenkamp
Moving Professionals



TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	13626238
EAN	4040658013393
Valid tyre size	280 / 85 R 28
LI / SI / PR	118 A8 / 115 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	43,01
Recommended rim size	10
Permitted rim size	9
Maximum air pressure [bar].	1,60
Section width (mm)	292
Outer diameter of tyre [mm].	1187
Stat. radius (SLR) [mm]	542
Rolling circumference [mm].	3580
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
118 A8	1320	40		1,60	
115 B	1215	50		1,60	