

TYRES

Product group	Tyres	
Item number	13626255	
Valid tyre size	320 / 85 R 28	
LI / SI / PR	124 A8 / 121 B	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM600	



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.

- Low soil compaction.
- Optimal traction.



Technical Informations

Item number	13626255
EAN	8059971009316
Valid tyre size	320 / 85 R 28
LI / SI / PR	124 A8 / 121 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	57,26
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	1,60
Section width (mm)	329
Outer diameter of tyre [mm].	1255
Stat. radius (SLR) [mm]	566
Rolling circumference [mm].	3796
Tread depth (mm)	41,0
Number of lugs	21x2
Lug width (mm)	34
Tyre capacity 75% [ltr.]	157
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 A8	1600	40		1,60	
121 B	1450	50		1,60	