

TYRES

Product group	Tyres
Item number	13626267
Valid tyre size	360 / 70 R 28
LI / SI / PR	125 A8 / 125 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.

Technical Informations

Item number	13626267
EAN	8059971009521
Valid tyre size	360 / 70 R 28
LI / SI / PR	125 A8 / 125 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	62,00
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	1,60
Section width (mm)	352
Outer diameter of tyre [mm].	1246
Stat. radius (SLR) [mm]	568
Rolling circumference [mm].	3745
Tread depth (mm)	42,0
Number of lugs	18x2
Lug width (mm)	40
Tyre capacity 75% [ltr.]	166
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A8	1650	40		1,60	
125 B	1650	50		1,60	