

TYRES

Product group	Tyres
Item number	13626330
Valid tyre size	600 / 65 R 28
LI / SI / PR	154 D / 151 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800HS
Sonderpostenkategorie	DA



Notes and features

- Wide radial tractor tyre of the 65 series for high-performance tractors of approximately 100-220 hp.
- Suitable for the heaviest farm work and frequent road use.
- Approved for 70 km/h and increased loading capacity compared with the TM 800.
- Large contact area ensures that more lugs interlock with the ground and thus improve traction.

Technical Informations

Item number	13626330
EAN	4040658037122
Valid tyre size	600 / 65 R 28
LI / SI / PR	154 D / 151 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800HS
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	151,00
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	2,40
Section width (mm)	590
Outer diameter of tyre [mm].	1491
Stat. radius (SLR) [mm]	660
Rolling circumference [mm].	4490
Tread depth (mm)	52,0
Lug width (mm)	48,0
Tyre capacity 75% [ltr.]	480
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		2,40	
151 E	3450	70		2,40	