

TYRES

Product group	Tyres
Item number	13626371
Valid tyre size	460 / 85 R 30
LI / SI / PR	145 A8 / 142 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp
Moving Professionals



TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	13626371
EAN	8059971013368
Valid tyre size	460 / 85 R 30
LI / SI / PR	145 A8 / 142 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	121,28
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	1,60
Section width (mm)	475
Outer diameter of tyre [mm].	1544
Stat. radius (SLR) [mm]	691
Rolling circumference [mm].	4678
Tread depth (mm)	53,0
Lug width (mm)	43
Tyre capacity 75% [litr.]	389
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		1,60	
142 B	2650	50		1,60	