

TYRES

Product group	Tyres
Item number	13626390
Valid tyre size	650 / 75 R 32
LI / SI / PR	172 A8
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM2000



Notes and features

- Radial tyre for the heaviest harvesters.
- High air volume and large contact area ensure high loading capacities, even at low inflation pressure.
- Large, solid lugs enable optimum slope / lateral stability.
- Special rubber compound minimises tread pattern damage (e.g. by corn stubble).

Technical Informations

Item number	13626390
EAN	8059971014686
Valid tyre size	650 / 75 R 32
Alternative size 1	24.5R32
LI / SI / PR	172 A8
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM2000
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	267,77
Recommended rim size	20
Maximum air pressure [bar].	3,20
Section width (mm)	662
Outer diameter of tyre [mm].	1817
Stat. radius (SLR) [mm]	805
Rolling circumference [mm].	5495
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		3,20	