

## **TYRES**

Product group	Tyres	
Item number	13626398	
Valid tyre size	710 / 75 R 32	
LI / SI / PR	177 A8	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM2000	



## Notes and features

- Radial tyre for the heaviest harvesters.
- High air volume and large contact area ensure high loading capacities, even at low inflation pressure.
- Large, solid lugs enable optimum slope / lateral stability.
- Special rubber compound minimises tread pattern damage (e.g. by corn stubble).



## **Technical Informations**

Item number	13626398
EAN	8059971015089
Valid tyre size	710 / 75 R 32
LI / SI / PR	177 A8
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM2000
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	288,00
Recommended rim size	23
Maximum air pressure [bar].	3,20
Section width (mm)	735
Outer diameter of tyre [mm].	1850
Stat. radius (SLR) [mm]	830
Rolling circumference [mm].	5595
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 A8	7300	40		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.