

## **TYRES**

Product group	Tyres	
Item number	13626403	
Valid tyre size	IF 800 / 70 R 32 CFO	
LI / SI / PR	182 A8	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM3000	



## Notes and features

- Radial tractor tyre featuring IF technology and Trelleborg's BLUE TYRE technology for state-of-the-art harvesters.
- 20% higher load capacity at constant inflation pressure or 20% lower inflation pressure with the same payload compared with standard tyres.
- Suitable for cyclic field operation (CFO = Cyclic Field Operation).
- New tread pattern design and further improved casing maximise load capacity and soil protection.
- Increases harvest productivity.



## **Technical Informations**

Item number	13626403
EAN	8059971015362
Valid tyre size	IF 800 / 70 R 32 CFO
LI / SI / PR	182 A8
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM3000
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	341,00
Recommended rim size	27
Maximum air pressure [bar].	2,40
Section width (mm)	775
Outer diameter of tyre [mm].	1950
Stat. radius (SLR) [mm]	850
Rolling circumference [mm].	5845
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 A8	8500	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.