

## TYRES

Product group	Tyres
Item number	13626420
Valid tyre size	420 / 85 R 34
LI / SI / PR	142 A8 / 139 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp  
Moving Professionals



## Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

## Technical Informations

Item number	13626420
EAN	8059971004755
Valid tyre size	420 / 85 R 34
Alternative size 1	16.9R34
LI / SI / PR	142 A8 / 139 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	112,70
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	438
Outer diameter of tyre [mm].	1578
Stat. radius (SLR) [mm]	715
Rolling circumference [mm].	4745
Tread depth (mm)	50,0
Lug width (mm)	45
Tyre capacity 75% [ltr.]	355
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		1,60	
139 B	2430	50		1,60	