

TYRES

Product group	Tyres
Item number	13626425
Valid tyre size	420 / 85 R 34
LI / SI / PR	142 A8 / 139 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Sonderpostenkategorie	DA



Bohnenkamp
Moving Professionals


TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	13626425
EAN	4040658063459
Valid tyre size	420 / 85 R 34
Alternative size 1	16.9R34
LI / SI / PR	142 A8 / 139 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	104,15
Recommended rim size	W15L
Permitted rim size	W14L, DW14L, DW15L
Maximum air pressure [bar].	1,60
Section width (mm)	438
Outer diameter of tyre [mm].	1578
Stat. radius (SLR) [mm]	715
Rolling circumference [mm].	4745
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		1,60	
139 B	2430	50		1,60	