

TYRES

Product group	Tyres	
Item number	13626432	
Valid tyre size	480 / 70 R 34	
LI / SI / PR	143 A8 / 143 B	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM700	





Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.



Technical Informations

Item number	13626432
EAN	8059971002188
Valid tyre size	480 / 70 R 34
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	118,50
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	468
Outer diameter of tyre [mm].	1580
Stat. radius (SLR) [mm]	716
Rolling circumference [mm].	4720
Tread depth (mm)	52,0
Number of lugs	20x2
Lug width (mm)	48
Tyre capacity 75% [ltr.]	389
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40		1,60	
143 B	2725	50		1,60	