Bohnenkamp Moving Professionals

14.03.2025

TYRES

| Product group | Tyres | |
|-----------------|---------------|--|
| Item number | 13626470 | |
| Valid tyre size | 600 / 70 R 34 | |
| LI / SI / PR | 160 D / 157 E | |
| TL/TT | TL | |
| Brand | Trelleborg | |
| Tread pattern | ТМ900НР | |



Notes and features

- The TM 900 High Power was developed specifically for the biggest agricultural machines and high-performance tractors.
- It offers extremely high load capacity.

- Due to its special design, the tyre transmits the vehicle's high torque and enables high traction on all soils.
- It is characterised through extraordinarily high ride comfort and safety.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 13626470 |
|------------------------------|---------------|
| | 13020470 |
| EAN | 8059971013764 |
| Valid tyre size | 600 / 70 R 34 |
| LI / SI / PR | 160 D / 157 E |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | ТМ900НР |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 205,00 |
| Recommended rim size | 18 |
| Permitted rim size | 20 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 600 |
| Outer diameter of tyre [mm]. | 1685 |
| Stat. radius (SLR) [mm] | 755 |
| Rolling circumference [mm]. | 5105 |
| Tread depth (mm) | 55,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 160 D | 4500 | 65 | | 2,40 | |
| 157 E | 4125 | 70 | | 2,40 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.