

TYRES

Product group	Tyres	
Item number	13626538	
Valid tyre size	380 / 90 R 50	
LI / SI / PR	151 A8 / 151 B	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM100	



Notes and features

- Particularly suitable for work on row crops.
- Narrow radial tyre.

Good ride comfort.



Technical Informations

Item number	13626538
EAN	8059971001044
Valid tyre size	380 / 90 R 50
LI / SI / PR	151 A8 / 151 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM100
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	133,00
Recommended rim size	12
Permitted rim size	11, 13
Maximum air pressure [bar].	2,40
Section width (mm)	380
Outer diameter of tyre [mm].	1945
Stat. radius (SLR) [mm]	890
Rolling circumference [mm].	5885
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		2,40	
151 B	3450	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.