Bohnenkamp Moving Professionals

14.03.2025

TYRES

Product group	Tyres
Item number	13626544
Valid tyre size	380 / 90 R 54
LI / SI / PR	152 A8 / 152 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM100



Notes and features

- Particularly suitable for work on row crops.
- Good ride comfort.

• Narrow radial tyre.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13626544
EAN	8059971001082
Valid tyre size	380 / 90 R 54
LI / SI / PR	152 A8 / 152 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM100
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	150,00
Recommended rim size	12
Permitted rim size	11, 13
Maximum air pressure [bar].	2,40
Section width (mm)	380
Outer diameter of tyre [mm].	2040
Stat. radius (SLR) [mm]	940
Rolling circumference [mm].	6175
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		2,40	
152 B	3550	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.