

TYRES

Product group	Tyres	
Item number	13626551	
Valid tyre size	320 / 85 R 38	
LI / SI / PR	129 A8 / 126 B	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM600	



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.

- Low soil compaction.
- Optimal traction.



Technical Informations

Item number	13626551
EAN	8059971004953
Valid tyre size	320 / 85 R 38
LI / SI / PR	129 A8 / 126 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	69,10
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	1,60
Section width (mm)	325
Outer diameter of tyre [mm].	1520
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4605
Tread depth (mm)	46,0
Lug width (mm)	28
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 A8	1850	40		1,60	
126 B	1700	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.