

TYRES

Product group	Tyres
Item number	13626552
Valid tyre size	320 / 85 R 38
LI / SI / PR	129 A8 / 136 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Sonderpostenkategorie	DA



Bohnenkamp
Moving Professionals



TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	13626552
EAN	4040658074394
Valid tyre size	320 / 85 R 38
LI / SI / PR	129 A8 / 136 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	82,00
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	1,60
Section width (mm)	325
Outer diameter of tyre [mm].	1520
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4605
Tread depth (mm)	46,0
Lug width (mm)	28
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 A8	1850	40		1,60	
136 B	2240	50		1,60	