

TYRES

Product group	Tyres
Item number	13626562
Valid tyre size	340 / 85 R 38
LI / SI / PR	133 A8 / 130 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Sonderpostenkategorie	DA



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	13626562
EAN	4040658075643
Valid tyre size	340 / 85 R 38
Alternative size 1	13.6R38
LI / SI / PR	133 A8 / 130 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	82,00
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	1,60
Section width (mm)	353
Outer diameter of tyre [mm].	1543
Stat. radius (SLR) [mm]	710
Rolling circumference [mm].	4665
Tread depth (mm)	44,0
Lug width (mm)	35
Tyre capacity 75% [ltr.]	224
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		1,60	
130 B	1900	50		1,60	