

TYRES

Product group	Tyres
Item number	13626579
Valid tyre size	380 / 85 R 38
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Sonderpostenkategorie	DA





Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.

- Low soil compaction.
- Optimal traction.



Technical Informations

Item number	13626579
EAN	4040658057892
Valid tyre size	380 / 85 R 38
Alternative size 1	14.9R38
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	99,00
Recommended rim size	13
Permitted rim size	11, 12
Maximum air pressure [bar].	2,40
Section width (mm)	400
Outer diameter of tyre [mm].	1610
Stat. radius (SLR) [mm]	730
Rolling circumference [mm].	4900
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		2,40	
144 B	2800	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.