Bohnenkamp Moving Professionals

12.03.2025

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 13626580 |
| Valid tyre size | 380 / 85 R 38 |
| LI / SI / PR | 144 A8 / 144 B |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | ТМ600 |



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.

- Low soil compaction.
- Optimal traction.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 13626580 | |
|------------------------------|----------------------------|--|
| EAN | 8059971013429 | |
| Valid tyre size | 380 / 85 R 38 | |
| Alternative size 1 | 14.9R38 | |
| LI / SI / PR | 144 A8 / 144 B | |
| TL/TT | TL | |
| Brand | Trelleborg | |
| Tread pattern | TM600 | |
| Antistatic | No | |
| Tyre colour | Black | |
| ECE regulation number | not necessary | |
| Nettogewicht [kg] (gültig) | 108,85 | |
| Recommended rim size | W13 | |
| Permitted rim size | W11, W12, DW11, DW12, DW13 | |
| Maximum air pressure [bar]. | 2,40 | |
| Section width (mm) | 400 | |
| Outer diameter of tyre [mm]. | 1610 | |
| Stat. radius (SLR) [mm] | 730 | |
| Rolling circumference [mm]. | 4900 | |
| Tyre capacity 75% [ltr.] | 224 | |
| E-Ready | No | |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 144 A8 | 2800 | 40 | | 2,40 | |
| 144 B | 2800 | 50 | | 2,40 | |

12.03.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.