

TYRES

Product group	Tyres
Item number	13626627
Valid tyre size	600 / 65 R 38
LI / SI / PR	153 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800
Sonderpostenkategorie	DA





Notes and features

- Modern agricultural tyre, approved up to 65 km/h.
- Maximum performance in the field due to extra-large contact area.
- High level of comfort.
- Long service life.



Technical Informations

Item number	13626627
EAN	4040658066696
Valid tyre size	600 / 65 R 38
LI / SI / PR	153 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	168,06
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	590
Outer diameter of tyre [mm].	1745
Stat. radius (SLR) [mm]	785
Rolling circumference [mm].	5210
Tread depth (mm)	55,0
Lug width (mm)	46
Tyre capacity 75% [ltr.]	590
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 D	3650	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.