

TYRES

Product group	Tyres
Item number	13626636
Valid tyre size	710 / 70 R 38
LI / SI / PR	171 D / 168 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800HS



Notes and features

- Wide radial tractor tyre of the 65 series for high-performance tractors of approximately 100-220 hp.
- Suitable for the heaviest farm work and frequent road use.
- Approved for 70 km/h and increased loading capacity compared with the TM 800.
- Large contact area ensures that more lugs interlock with the ground and thus improve traction.

Technical Informations

Item number	13626636
EAN	8059971003406
Valid tyre size	710 / 70 R 38
LI / SI / PR	171 D / 168 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800HS
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	306,00
Recommended rim size	23
Permitted rim size	25
Maximum air pressure [bar].	2,40
Section width (mm)	711
Outer diameter of tyre [mm].	1973
Stat. radius (SLR) [mm]	884
Rolling circumference [mm].	5928
Tread depth (mm)	62,0
Lug width (mm)	45
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
171 D	6150	65		2,40	
168 E	5600	70		2,40	