Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	13626640
Valid tyre size	650 / 75 R 38
LI / SI / PR	169 D / 166 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	ТМ900НР



Notes and features

- The TM 900 High Power was developed specifically for • the biggest agricultural machines and high-performance tractors.
- It offers extremely high load capacity. .

- Due to its special design, the tyre transmits the vehicle's . high torque and enables high traction on all soils.
- It is characterised through extraordinarily high ride • comfort and safety.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13626640
EAN	8059971013498
Valid tyre size	650 / 75 R 38
LI / SI / PR	169 D / 166 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	ТМ900НР
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	281,00
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	676
Outer diameter of tyre [mm].	1940
Stat. radius (SLR) [mm]	855
Rolling circumference [mm].	5840
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		2,40	
166 E	5300	70		2,40	