

TYRES

Product group	Tyres
Item number	13626648
Valid tyre size	600 / 65 R 42
LI / SI / PR	154 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- Modern agricultural tyre, approved up to 65 km/h.
- Maximum performance in the field due to extra-large contact area.
- High level of comfort.
- Long service life.

Technical Informations

Item number	13626648
EAN	8059971004120
Valid tyre size	600 / 65 R 42
LI / SI / PR	154 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	201,00
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	590
Outer diameter of tyre [mm].	1847
Stat. radius (SLR) [mm]	830
Rolling circumference [mm].	5580
Tread depth (mm)	55,0
Lug width (mm)	49
Tyre capacity 75% [litr.]	637
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		1,60	