

TYRES

Product group	Tyres	
Item number	13626657	
Valid tyre size	900 / 60 R 38	
LI / SI / PR	178 D / 175 E	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	ТМ900НР	
Sonderpostenkategorie	DA	





Notes and features

- The TM 900 High Power was developed specifically for the biggest agricultural machines and high-performance tractors.
- It offers extremely high load capacity.

- Due to its special design, the tyre transmits the vehicle's high torque and enables high traction on all soils.
- It is characterised through extraordinarily high ride comfort and safety.



Technical Informations

Item number	13626657
EAN	4040658060113
Valid tyre size	900 / 60 R 38
LI / SI / PR	178 D / 175 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	ТМ900НР
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	380,00
Recommended rim size	28
Permitted rim size	27, 30
Maximum air pressure [bar].	2,40
Section width (mm)	905
Outer diameter of tyre [mm].	2040
Stat. radius (SLR) [mm]	915
Rolling circumference [mm].	6180
Tread depth (mm)	62,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 D	7500	65		2,40	
175 E	6900	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.