

TYRES

Product group	Tyres
Item number	13626662
Valid tyre size	620 / 70 R 42
LI / SI / PR	166 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700



Bohnenkamp
Moving Professionals



Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.

Technical Informations

Item number	13626662
EAN	8059971002409
Valid tyre size	620 / 70 R 42
LI / SI / PR	166 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	232,46
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	625
Outer diameter of tyre [mm].	1935
Stat. radius (SLR) [mm]	871
Rolling circumference [mm].	5855
Tread depth (mm)	58,0
Lug width (mm)	50
Tyre capacity 75% [ltr.]	789
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		2,40	