Bohnenkamp Moving Professionals

14.03.2025

TYRES

Product group	Tyres
Item number	13626716
Valid tyre size	650 / 65 R 42
LI / SI / PR	158 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	ТМ800
Sonderpostenkategorie	DA



Notes and features

- Modern agricultural tyre, approved up to 65 km/h.
- Maximum performance in the field due to extra-large contact area.
- High level of comfort.
- Long service life.

Bohnenkamp Moving Professionals

Technical Informations

Item number	13626716
EAN	4040658060137
Valid tyre size	650 / 65 R 42
LI / SI / PR	158 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM800
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	242,40
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	645
Outer diameter of tyre [mm].	1913
Stat. radius (SLR) [mm]	860
Rolling circumference [mm].	5780
Tread depth (mm)	59,0
Number of lugs	23x2
Lug width (mm)	49
Tyre capacity 75% [ltr.]	765
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.