

TYRES

Product group	Tyres
Item number	13626760
Valid tyre size	480 / 80 R 46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Bohnenkamp
Moving Professionals



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	13626760
EAN	8059971005028
Valid tyre size	480 / 80 R 46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	184,59
Recommended rim size	16
Maximum air pressure [bar].	2,40
Section width (mm)	495
Outer diameter of tyre [mm].	1964
Stat. radius (SLR) [mm]	887
Rolling circumference [mm].	5950
Tread depth (mm)	56,0
Lug width (mm)	27
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		2,40	
158 B	4250	50		2,40	