

TYRES

Product group	Tyres	
Item number	13626770	
Valid tyre size	520 / 85 R 46	
LI / SI / PR	158 A8 / 158 B	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM600	



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.

- Low soil compaction.
- Optimal traction.



Technical Informations

Item number	13626770
EAN	8059971005158
Valid tyre size	520 / 85 R 46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	217,20
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	535
Outer diameter of tyre [mm].	2045
Stat. radius (SLR) [mm]	905
Rolling circumference [mm].	6160
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		1,60	
158 B	4250	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.