

TYRES

Product group	Tyres
Item number	13627221
Valid tyre size	IF 650 / 60 R 34
LI / SI / PR	159 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000HP
Sonderpostenkategorie	DA



Bohnenkamp
■ ■ ● Moving Professionals


TRELLEBORG

Notes and features

- IF tyre for tractors in the highest performance range (from 250 hp approx.).
- 20% higher load capacity at constant inflation pressure or 20% lower inflation pressure with the same payload compared with standard tyres.
- Wide contact area enables optimal soil protection and can thus increase crop yields.
- Operating costs are reduced through very good traction and low rolling resistance.

Technical Informations

Item number	13627221
EAN	4040658076954
Valid tyre size	IF 650 / 60 R 34
LI / SI / PR	159 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1000HP
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	207,00
Recommended rim size	23
Maximum air pressure [bar].	1,60
Section width (mm)	645
Outer diameter of tyre [mm].	1660
Stat. radius (SLR) [mm]	725
Rolling circumference [mm].	4955
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 D	4375	65		1,60	